

LD RHINORIG By Fabritek Company

Overview

The LD Rhino Rig is an affordable water well drilling rig that combines the proven drilling technology of cable tool drilling with today's reliable hydraulic drive technology. What is produced is a rig designed for drilling in all types of geology, specifically in developing countries. This rig can drill through both rock and unconsolidated formations to a depth in excess of 400 feet (137 meters). A typical well of approximately 150 feet (50 meters) requires only about 20 gallons (75 liters) of gasoline and can be completed in one week. Operation of the rig requires little training and can be set up and operated by one person.



Specifications

Weight (less stem & tool): 6,500 lbs (2950 kg)

Trailer Weight Capacity: 15,000 lbs (6800 kg)

Trailer Brakes: 4 wheel hydraulic Mast Height: 29 ft (8.8 m) usable Sandline Cable: 500 ft (152.4 m); 3/8 in. (1 cm) diameter Mainline Cable: 500 ft (152.4 m); 5/8 in. (1.6 cm) diameter (adjustable auto-feed for mainline) Engine: 21 horsepower gasoline Honda electric start

18 amp charger

Welder (optional): 150 amp arc welder

Hydraulic Oil Tank: 20 gal (75 L) capacity

Stroke: 22 in. (56 cm) stroke, 58 strokes/min

Water: 40 gal (151 L) water storage with pressure pump

Fuel: 24 gal (90 L) fuel tank; approximately 12 hrs of continuous operation

3 Square Jacks: Each rated at 25,000 lbs (11,400 kg)

4 Spool Hydraulic Control: Mast, Sandline, Mainline, Walking Beam Feed: Adjustable auto feed for mainline







Advantages

- One person operation
- Can be setup and drilling in under 30 minutes
- Drills through rock easily at rates of 1 3.3 ft/hr (0.3 – 1 m/hr)
- Mobile enough to reach remote areas
- No mud pump, air compressor or water truck required
- Drills unconsolidated formations at a rate of about 3.3 – 9.8 ft/hr (1 – 3 m/hr)
- Accommodates bit sizes of 3.75 in. (9.5 cm) to 10 inch (25.4 cm)
- Powder coat finish for long lasting durability
- 30 ft (9.1 m) mast, easy casing and pump install
- Remove casing confidently with 20,000 lb (9,100 kg) lift capability
- Spare parts available worldwide

Pricing & Shipping

Financing Options Dimensions: 9.3 x 7.6 x 7 ft (2.82 x 2.31 x 2.13 m) Weight: 6,500 lbs (2950 kg) Note: Ships two rigs in a standard 40 ft (12.2 m) shipping container

Awards

At the World Water Day event on March 21, 2014, The US State Department recognized the LDT 360 as an exemplary water technology for developing countries.



Contact us to see if the LD Rhino Rig is right for you!

Rhino-Rig.com 540-869-1150 Sales@fabritek.com